




YOUR PARTNER IN METALWORKING

# MG ITALY PRODUCTS e MACHINERY 2023

"Teamwork is the ability to work together toward a common vision. The ability to direct individual accomplishments toward organizational objectives". (A.Carnegie)

*mgitaly.it*





YOUR PARTNER IN METALWORKING

MG philosophy:

***“Competition is not about what  
companies produce, but about what  
they are able to add to the product”***



# Index

Company, Mission & Vision	P.	04
Company Quality, Experience & Expertise	P.	05
Company Profile, Structure & Partnership	P.	06 - 07
Business Unit	P.	08 - 11
Extruded technology	P.	13 - 40
Welded technology	P.	41 - 47
Assembled technology	P.	48 - 61
"HEATSINK PLUS" technology	P.	62 - 65
Water technology	P.	66 - 67
Dissipation technology MGSKIVED	P.	68 - 69
PV fasteners	P.	70 - 82
Processes – Machining	P.	83 - 85



YOUR PARTNER IN METALWORKING


***Leading group in mechanical machining and automation worldwide.  
Over the years, our group has remained fully committed to being a  
top-level manufacturer in high-precision machining and high-quality  
electromechanical components.***



**100 +**  
Employees



**3**  
Production plants



**4.00 Sqm**  
Surface



**25**  
Production lines

MG develops and produces heat dissipation systems with different technologies, air, liquid, and many others. Our organization is engaged in different sectors: Continuous Facades, Furniture, Transportation, Cooling Company, Automotive, Electronics, Civil and Military Defence, Design Lighting, Motors, Aerospace, Photovoltaic, many others.

Our group today covers an area of 4,000 square meters with over 100 operators and employees and operates in the sector of precision machining for industries of various sectors making use of constantly updated infrastructures and production plants.



## ***Mission e vision***

Teamwork is the ability to work together toward a common vision.

The ability to direct individual accomplishments toward organizational objectives.





# Experience and Expertise

## *Technical expertise at the service of our customer*

Our technical staff, thanks to their considerable experience, will be able to deal reactively and with excellent quality and innovative solutions for any of your needs.

A unique service that has allowed us, over the years, to attract the attention of companies on a global level as well.

UNI EN ISO 9001:2015



## Company Quality

*Our organization is in continuous development,  
in a continuous search to improve each of its processes.*

Our Top Management is continuously and systematically involved in the implementation, maintenance, development and improvement of the Quality Management System.

In Quality Management System (QMS) which allows to guarantee the achievement of the set objectives and customer satisfaction, in compliance with the applicable reference Standards and Directives, as well as with the specific contractual requirements.



Regione Toscana



## OUR BASIC PRINCIPLES

- ✓ *Satisfaction and focus on customer needs*
- ✓ *Always improving products and services offered*
- ✓ *Compliance with the requirements specified by customers*
- ✓ *Compliance with ASD customer requirements*
- ✓ *Compliance with workplace safety regulations*
- ✓ *High healthy and safety standards and regulations*
- ✓ *ISO 9001 QMS*
- ✓ *International Management System*

# COMPANY PROFILE

In 40 years we have developed an extraordinary set of skills accompanied by the typical commitment of those who want to be leaders and always placing the customer and their needs at the center of their business decisions, we have worked hard to obtain gratifying results both professionally and socially with particular regard to environmental protection.

On these premises, the company management has invested considerable energy to instill a new corporate culture understood as a consolidated and widespread practice in all sectors of the company. An ethical culture whose fundamental pillars are found in the values that have always distinguished our Company.




## Company Structure

- ✓ Technical ability of operators to identify customer problems
- ✓ Many years of knowledge based on continuous technical updating and on maintaining high quality standards
- ✓ International team, English, German, Spanish and Russian native speakers
- ✓ Technical personnel with a notable and consolidated background gained through multiple and heterogeneous experiences in diversified sectors
- ✓ Carefully selected suppliers, according to a production chain system

# International partners, we are present in foreign markets

We have many years of knowledge based on continuous technical updating and on maintaining high quality standards in order to ensure high corporate competitiveness. The company management has thought of a flexible and adequate structure built according to the suggestions of the customers to better assist them.

- 1** **Spain**  
Aerospace, Furniture, Nautical
- 2** **USA**  
Dissipation, Electric Mobility
- 3** **Germany**  
Aerospace, Electronics, Automotive
- 4** **Slovakia**  
Industry, Electronics, Renewable Energy
- 5** **Italy**  
Industry, Electronics, Renewable Energy




# Business Unit

---

Our main strength is our highly qualified personnel who, having the latest generation machinery, the result of constant investments, are able to achieve increasingly stringent quality standards.

The continuous refinement of production technologies, combined with the experience gained in more than forty years of mechanical machining, makes the company the ideal partner for customers operating in different application sectors.



## Business Unit: **BusBars e Connections**

---

### **FLEXIBLE BUSBARS**

Round, tubular and flat copper braids are an extra flexible conductor for all electrical connection needs, including power, earth and equipotential connections.


The new copper-insulated flexible bar, produced in a new and advanced production plant, is the only flexible bar and stands out, through the innovative features, for its high flexibility, excellent appearance and easy use.

The “barrel” insulator is used as an insulating support for active conductors, a support for electrical equipment, a spacer and/or stiffening element of a system made up of conductor bars (in copper and/or aluminium).

### **RIGID BUSBARS**

In our Electronics division, we make all the connection components in copper and not only. The materials are chosen according to the needs each project.

We have various busbar solutions, which are designed together with our customers. Each project is created according to your needs.



## Business Unit: **DIE CASTING**

---

We operate in the aluminum die-casting sector and thanks to the great experience accumulated over the last few decades, we offer a complete service, from the creation of the mold to the supply of the machined and tested piece.

We are able to collect all the requests from our customers, having the possibility of carrying out mechanical machining on die-cast parts, as well as performing aesthetic finishes.

Often, the customer prefers to commission the finishing activity, both to speed up the timing of the process and to have a single contact person and therefore not having to personally follow each phase.

Our Company is able to supply die-casting of any type of aluminum alloy.

In addition to the most used alloys (EN AB-43400, EN AB- 44300, EN AB-46000, EN AB-46100, EN AB-47100), we can use special alloys such as Silafont 36. All the molten aluminum in the central melting furnaces is then subjected to a degassing and slagging treatment with nitrogen and salts.



## Business Unit: **METAL PLATES**


---

### **3 fiber laser systems with automatic loading and unloading and 2 punching machines:**

- 1 Amada LCG-AJ 6KW laser cutting machine with automated warehouse
- 1 Amada ENSIS 3015 AJ 2KW laser cutting machine with automated warehouse
- 1 Trumpf TruLaser 5030 fiber (L76) laser cutting machine with automated warehouse
- 1 Trumpf 3000 punching machine with bar loading and unloading bench
- 1 Rainer punching machine

### **Bending:**

- 6 bending press brakes
- 1 automatic panel bender with flag bending system
- 1 HG ATC ARS Amada robotic bending cell
- 1 Starmatick robotic bending cell



## Business Unit: **INDUSTRIES**


---

This division deals with mechanical machining on CNC Milling and Turning centers, based on the executive drawings provided by our customers or by our technical office.

The machinery present in our production lines are all of the latest generation and constantly updated to guarantee high-performance and competitive processes on the market.

The entire production process is monitored through our operational processes that allow you to have quality and timing control on all productions.

Further information can be found on our website [www.mgitaly.it](http://www.mgitaly.it)



## Business Unit: **ELECTRONICS**

---

### **EXTRUDED**

We are one of the world's leading manufacturers of aluminum heat sinks. Our main activities include the study, design and development of profiles aimed at the creation of finished products.

Innovative and flexible, we are able to provide customized solutions for any type of application. We produce extruded heat sinks, assembled, according to the requests of our customers.

We have been developing new ideas for over 40 years and our product range includes more than a thousand extruded aluminum profiles and more than 20,000 finished products. You can find out more about these aspects on our website: [www.mgitaly.it](http://www.mgitaly.it)

---

### **Cold\_Plate**

The COLD\_PLATE solution is the optimal solution for efficiently managing complex systems with high concentrated powers. Water cooling is thus becoming the ideal alternative for dissipating high powers. This system avoids noise and problems due to vibrations, considering that this dissipation system can also be used in dusty environments where forced air cannot be used.





## Business Unit: **WELDINGS**

Laser, tig, mig/mag and a dedicated robot for high quality welding services.

- 1 Welding Robot
- TIG & MIG welding machines



## Business Unit: **Plastic materials**

### **Plastic materials for electrical insulators and mechanical components**

Once in operation, every plant requires a powerful and reliable electrical system. Generators, transformers and switchboards must always be coordinated with the expected performance and structure of the installation. We help you in the construction with our thermosetting semi-finished products, which have been used in the electrical industry all over the world for over 40 years. Highly resistant to electrical, mechanical and thermal loads, with our materials you develop generators, transformers and switchboards with high operational safety.

#### **Your benefits**

High operational safety - Long duration - Low flammability - High electrical stability - High mechanical stability - High thermal resistance

#### **Application**

Electrical systems High power systems Energy cooling systems, UPS, Systems with high operating temperatures.

#### **Used materials:**

Gpo3  
Pvc  
Lexan  
Vetronite




## Business Unit: **MILLING**

---

With a fleet of over 15 high-level machining centres, MG proposes itself as prime contractor for carrying out mechanical machining to customer drawings, in order to guarantee the production of high precision parts with limited time and cost.

All CNC machines are always manned by assigned personnel who are exclusively responsible for the good execution and dimensional control of the product they are making.

To make this way of working possible, the department heads supervise the production cycle, while other qualified personnel carry out some necessary and fundamental operations.



## Business Unit: **TURNING**

---

In the field of high precision machining, MG also offers CNC turning service. We have state-of-the-art CNC turning machines.

Thanks to the computerized detection of work phases, the company can guarantee constant real-time control of the progress of production, together with the immediate traceability of the processes carried out or still in progress.



# EXTRUDED TECHNOLOGY

*The aluminum extrusion process makes it possible to obtain profiles of infinite, even complex shapes.*

By varying the shape of the profile, changing the contact surface with the air and, consequently, the dissipation capacity.


By varying the shape of the profile, changing the contact surface with the air and, consequently, the dissipation capacity.

---

The extruded heat sinks are presented subdivided by shape (T, H, L, K, E, U, P), width and height, and organized in increasing order of size. MG follows mechanical processes following the customer's requests, guaranteeing reliability and quality of the finished product.

CODE


**DE15\_20**



Kg/mt	0.25 Kg/mt
L	15 mm
H	20 mm
Rth,F	4.750 K/W
Rth,N	14.10 K/W
Alloy	6061

CODE


**DE20\_15**



Kg/mt	0.24 Kg/mt
L	20 mm
H	15 mm
Rth,F	5.590 K/W
Rth,N	16.60 K/W
Alloy	6061

CODE


**DE21.3\_91.3**



Kg/mt	1.898
L	21.3 mm
H	91.3 mm
Alloy	6061

CODE


**DE28\_32**



Kg/mt	0.73 Kg/mt
L	28 mm
H	32 mm
Rth,F	2.650 K/W
Rth,N	7.80 K/W
Alloy	6061

CODE


**DE29\_12**



Kg/mt	0.35 Kg/mt
L	29 mm
H	11.50 mm
Rth,F	3.850 K/W
Rth,N	11.50 K/W
Alloy	6061


CODE

**DE30\_28**



Kg/mt	0.98 Kg/mt
L	30 mm
H	28 mm
Rth,F	2.889 K/W
Rth,N	9.30 K/W
Alloy	6061

**CODE** DE30\_47




Kg/mt	1,3 Kg/mt
L	30 mm
H	47 mm
Rth,F	4.29 K/W
Rth,N	2.99 K/W
Alloy	6060

**CODE** DE31.5\_7.4




Kg/mt	5.068 Kg/mt
L	31.5 mm
H	7.4 mm
Alloy	6061

**CODE** DE31.7\_50




Kg/mt	1.161 Kg/mt
L	31.7 mm
H	50 mm
Rth,F	1.86 K/W
Rth,N	5.6 K/W
Alloy	6061

**CODE** DE34.5\_12




Kg/mt	0.43 Kg/mt
L	34.5 mm
H	12.50 mm
Rth,F	3.450 K/W
Rth,N	10.20 K/W
Alloy	6061

**CODE** DE34\_60




Kg/mt	2.84 Kg/mt
L	34 mm
H	60 mm
Rth,F	1.170 K/W
Rth,N	3.50 K/W
Alloy	6061

**CODE** DE35\_44




Kg/mt	2 Kg/mt
L	35 mm
H	44 mm
Rth,F	1.880 K/W
Rth,N	5.60 K/W
Alloy	6061

**CODE** DE38\_20




Kg/mt	0.71 Kg/mt
L	38 mm
H	20 mm
Rth,F	3.250 K/W
Rth,N	9.50 K/W
Alloy	6061

**CODE** DE40\_35




Kg/mt	1.73 Kg/mt
L	40 mm
H	35 mm
Rth,F	1.17 K/W
Rth,N	3.50 K/W
Alloy	6061

**CODE** DE40\_60




Kg/mt	3.41 Kg/mt
L	40 mm
H	1.450 K/W
Rth,F	4.30 K/W
Rth,N	60 mm
Alloy	6061

**CODE** DE44\_11




Kg/mt	0.56 Kg/mt
L	44 mm
H	11 mm
Rth,F	3.250 K/W
Rth,N	9.09 K/W
Alloy	6061

**CODE** DE45\_14



Kg/mt	0.55 Kg/mt
L	45 mm
H	14 mm
Rth,F	3.210 K/W
Rth,N	9.70 K/W
Alloy	6061

**CODE** DE46-33




Kg/mt	2.077 Kg/mt
L	100 mm
Rth,F	0.87 K/W
Rth,N	2.58 K/W
H	33 mm



CODE


**DE46-33**



Kg/mt	2.077 Kg/mt
L	100 mm
Rth,F	0.87 K/W
Rth,N	2.58 K/W
H	33 mm

CODE


**DE48\_33**



Kg/mt	1.45 Kg/mt
L	48 mm
H	33 mm
Rth,F	1.990 K/W
Rth,N	5.90 K/W
Alloy	6061

CODE


**DE48\_40**



Kg/mt	2.45 Kg/mt
L	48 mm
H	40 mm
Rth,F	1.240 K/W
Rth,N	3.70 K/W
Alloy	6061

CODE


**DE50\_24**



Kg/mt	1.03 Kg/mt
L	50 mm
H	2.750 K/W
Rth,F	8.30 K/W
Rth,N	24 mm
Alloy	6061

CODE


**DE50\_28**



Kg/mt	1.65 Kg/mt
L	50 mm
H	28 mm
Rth,F	2.410 K/W
Rth,N	7.20 K/W
Alloy	6061


CODE

**DE52\_20**




Kg/mt	0.73 Kg/mt
L	52 mm
H	0.259 K/W
Rth,F	6.75 K/W
Rth,N	20 mm
Alloy	6061

**CODE** DE52\_40




Kg/mt	2.79 Kg/mt
L	52 mm
H	40 mm
Rth,F	1.050 K/W
Rth,N	3.10 K/W
Alloy	6061

**CODE** DE54\_38




Kg/mt	2.20 Kg/mt
L	54 mm
H	38 mm
Rth,F	4.50 K/W
Rth,N	4.50 K/W
Alloy	6061

**CODE** DE60\_24




Kg/mt	1.22 Kg/mt
L	60 mm
H	2.210 K/W
Rth,F	6.03 K/W
Rth,N	24 mm
Alloy	6061

**CODE** DE65\_19.5



Kg/mt	1.25 Kg/mt
L	65 mm
H	1.989 K/W
Rth,F	5.85 K/W
Rth,N	19.50 mm
Alloy	6061

**CODE** DE66\_30




Kg/mt	1,742 Kg/mt
L	66 mm
Rth,F	0,99 K/W
Rth,N	2,9 K/W
H	30 mm

**CODE** DE66\_33




Kg/mt	2.43 Kg/mt
L	66 mm
H	33 mm
Rth,F	1.480 K/W
Rth,N	4.40 K/W
Alloy	6061

**CODE** DE66\_40




Kg/mt	3.47 Kg/mt
L	66 mm
H	40 mm
Rth,F	0.990 K/W
Rth,N	3.10 K/W
Alloy	6061

**CODE** DE68\_90




Kg/mt	8.66 Kg/mt
L	68 mm
H	90 mm
Rth,F	0.411 K/W
Rth,N	1.22 K/W

**CODE** DE70\_132




Kg/mt	13.22 Kg/mt
L	70 mm
H	132 mm
Rth,F	0.830 K/W
Rth,N	2.25 K/W
Alloy	6061

**CODE** DE80\_14




Kg/mt	1.18 Kg/mt
L	80 mm
H	14 mm
Rth,F	1.395 K/W
Rth,N	4.05 K/W
Alloy	6061

**CODE** DE80\_24




Kg/mt	1.72 Kg/mt
L	80 mm
H	24 mm
Rth,F	1.830 K/W
Rth,N	5.40 K/W
Alloy	6061

**CODE** DE82\_32




Kg/mt	2.99 Kg/mt
L	82 mm
H	32 mm
Rth,F	0.670 K/W
Rth,N	2.60 K/W
Alloy	6061

**CODE** DE84\_14




Kg/mt	1,95 Kg/mt
L	80 mm
Rth,F	3,45 K/W
Rth,N	10,2 K/W
H	14 mm
Alloy	6060

**CODE** DE88\_35




Kg/mt	2,80 Kg/mt
L	88 mm
H	35 mm
Rth,F	1,395 K/W
Rth,N	4,05 K/W
Alloy	6061

**CODE** DE90\_29.5




Kg/mt	1,86 Kg/mt
L	90 mm
H	29,50 mm
Rth,F	1,650 K/W
Rth,N	4,90 K/W
Alloy	6061

**CODE** DE94\_14\_A




Kg/mt	1,64 Kg/mt
L	94 mm
H	14,50 mm
Rth,F	1,629 K/W
Rth,N	4,86 K/W
Alloy	6061

**CODE** DE95\_70




Kg/mt	7,25 Kg/mt
L	95 mm
H	70 mm
Rth,F	0,580 K/W
Rth,N	1,70 K/W
Alloy	6061

**CODE** DE96.5\_25




Kg/mt	3,934 Kg/mt
L	96,5 mm
H	25 mm
Rth,F	0,594 K/W
Rth,N	1,78 K/W

**CODE** DE97\_25.5




Kg/mt	3.40 Kg/mt
L	97 mm
H	25.5 mm
Rth,F	0.423 K/W
Rth,N	1.25 K/W
Alloy	6061

**CODE** DE100\_15




Kg/mt	2.16 Kg/mt
L	100 mm
H	15 mm
Rth,F	1.020 K/W
Rth,N	3.10 K/W
Alloy	6061

**CODE** DE100\_25




Kg/mt	2.66 Kg/mt
L	100 mm
H	25 mm
Rth,F	0.484 K/W
Rth,N	1.43 K/W
Alloy	6061

**CODE** DE100\_40




Kg/mt	5.12 Kg/mt
L	100 mm
H	40 mm
Rth,F	1.19 K/W
Rth,N	40 mm
Alloy	6061

**CODE** DE100\_50



Kg/mt	4.90 Kg/mt
L	100 mm
H	50 mm
Rth,F	1.125 K/W
Rth,N	3.24 K/W
Alloy	6061


**CODE** DE100\_95.2



Kg/mt	8.548 Kg/mt
L	100 mm
H	95.2 mm
Rth,F	0.47 K/W
Rth,N	1.4 K/W
Alloy	6061




**CODE** DE100\_120




Kg/mt	15.64 Kg/mt
L	100 mm
H	120 mm
Rth,F	0.790 K/W
Rth,N	2.30 K/W
Alloy	6061

**CODE** DE105\_38




Kg/mt	2.83 Kg/mt
L	105 mm
H	38 mm
Rth,F	1.210 K/W
Rth,N	3.60 K/W
Alloy	6061

**CODE** DE112\_72




Kg/mt	9.81 Kg/mt
L	112 mm
H	72 mm
Rth,F	0.590 K/W
Rth,N	1.62 K/W
Alloy	6061

**CODE** DE113\_37




Kg/mt	3.43 Kg/mt
L	113 mm
H	37 mm
Rth,F	0.790 K/W
Rth,N	2.30 K/W
Alloy	6061

**CODE** DE115\_33



Kg/mt	3.83 Kg/mt
L	115 mm
H	33.50 mm
Rth,F	0.880 K/W
Rth,N	2.43 K/W
Alloy	6061


**CODE** DE115\_80



Kg/mt	9.52 Kg/mt
L	115 mm
H	80 mm
Rth,F	0.510 K/W
Rth,N	1.50 K/W
Alloy	6061




**CODE** DE120\_40




Kg/mt	6.70 Kg/mt
L	120 mm
H	40 mm
Rth,F	0.620 K/W
Rth,N	1.71 K/W
Alloy	6061

**CODE** DE120\_40\_A




Kg/mt	6.51 Kg/mt
L	120 mm
H	40 mm
Rth,F	0.610 K/W
Rth,N	1.71 K/W
Alloy	6061

**CODE** DE120\_60




Kg/mt	8.37 Kg/mt
L	120 mm
H	60 mm
Rth,F	0.580 K/W
Rth,N	1.70 K/W
Alloy	6061

**CODE** DE120\_60\_B




Kg/mt	7.29 Kg/mt
L	120 mm
H	60 mm
Rth,F	0.560 K/W
Rth,N	1.70 K/W
Alloy	6061

**CODE** DE120\_63




Kg/mt	8.39 Kg/mt
L	120 mm
H	63 mm
Rth,F	0.540 K/W
Rth,N	60 K/W
Alloy	6061

**CODE** DE120\_64




Kg/mt	4.97 Kg/mt
L	120 mm
H	64 mm
Rth,F	1.010 K/W
Rth,N	2.79 K/W
Alloy	6061

**CODE** DE120\_70




Kg/mt	8.96 Kg/mt
L	120 mm
H	70 mm
Rth,F	0.410 K/W
Rth,N	1.20 K/W
Alloy	6061

**CODE** DE120\_120




Kg/mt	11.19 Kg/mt
L	120 mm
H	120 mm
Rth,F	0.251 K/W
Rth,N	0.74 K/W
Alloy	6061

**CODE** DE121\_58.5




Kg/mt	7.13 Kg/mt
L	121 mm
H	58.50 mm
Rth,F	0.580 K/W
Rth,N	1.70 K/W
Alloy	6061

**CODE** DE125\_76




Kg/mt	7.081 Kg/mt
L	125 mm
H	76 mm
Rth,F	0.275 K/W
Rth,N	0.84 K/W
Alloy	6061

**CODE** DE125\_125




Kg/mt	15.53 Kg/mt
L	125 mm
H	125 mm
Rth,F	0.390 K/W
Rth,N	1.08 K/W
Alloy	6061

**CODE** DE125\_135\_A




Kg/mt	17.61 Kg/mt
L	125 mm
H	135 mm
Rth,F	0.168 K/W
Rth,N	0.50 K/W
Alloy	6061

**CODE** DE125\_135\_B




Kg/mt	17.9 Kg/mt
L	125 mm
H	135 mm
Rth,F	0.38 K/W
Rth,N	1.10 K/W
Alloy	6061

**CODE** DE126\_63.5




Kg/mt	8.21 Kg/mt
L	126 mm
H	63.5 mm
Rth,F	0.549 K/W
Rth,N	1.62 K/W
Alloy	6061

**CODE** DE128\_57




Kg/mt	5.95 Kg/mt
L	128 mm
H	57 mm
Rth,F	0.522 K/W
Rth,N	1.53 K/W
Alloy	6061

**CODE** DE130\_52




Kg/mt	11.18 Kg/mt
L	130 mm
H	0.558 K/W
Rth,F	1.75 K/W
Rth,N	52 mm
Alloy	6061

**CODE** DE130\_84




Kg/mt	13.44 Kg/mt
L	130 mm
H	84 mm
Rth,F	0.470 K/W
Rth,N	1.26 K/W
Alloy	6061

**CODE** DE130\_130




Kg/mt	12.26 Kg/mt
L	130 mm
H	130 mm
Rth,F	0.680 K/W
Rth,N	1.89 K/W
Alloy	6061

**CODE** DE135\_25




Kg/mt	3.25 Kg/mt
L	135 mm
H	25 mm
Rth,F	0.650 K/W
Rth,N	1.90 K/W
Alloy	6061

**CODE** DE135\_135.5




Kg/mt	21.9 Kg/mt
L	135 mm
H	135.5 mm
Rth,F	0.18 K/W
Rth,N	0.81 K/W
Alloy	6061

**CODE** DE138\_40




Kg/mt	7.29 Kg/mt
L	138 mm
H	40 mm
Rth,F	0.650 K/W
Rth,N	1.90 K/W
Alloy	6061

**CODE** DE138\_50.5




Kg/mt	7.55 Kg/mt
L	138 mm
H	50.5 mm
Rth,F	0.51 K/W
Rth,N	1.50 K/W
Alloy	6061

**CODE** DE138\_62




Kg/mt	10.15 Kg/mt
L	138 mm
H	62 mm
Rth,F	2.75 K/W
Rth,N	1.69 K/W
Alloy	6060

**CODE** DE140\_26




Kg/mt	4.90 Kg/mt
L	100 mm
H	50 mm
Rth,F	1.125 K/W
Rth,N	3.24 K/W
Alloy	6061

**CODE** DE140\_90



Kg/mt	15.23 Kg/mt
L	140 mm
H	90 mm
Rth,F	0.459 K/W
Rth,N	1.35 K/W
Alloy	6061

**CODE** DE142\_120




Kg/mt	19.50 Kg/mt
L	142 mm
H	119.5 mm
Rth,F	0.380 K/W
Rth,N	1.08 K/W
Alloy	6061

**CODE** DE149.5\_9.2




Kg/mt	2.306 Kg/mt
L	149.5 mm
H	9.2 mm
Rth,F	0.58 K/W
Rth,N	1.7 K/W
Alloy	6061

**CODE** DE150\_27\_AF




Kg/mt	5.29 Kg/mt
L	150 mm
H	27 mm
Rth,F	0.513 K/W
Rth,N	1.53 K/W
Alloy	6061

**CODE** DE150\_27



Kg/mt	5.17 Kg/mt
L	150 mm
H	27 mm
Rth,F	0.522 K/W
Rth,N	1.53 K/W
Alloy	6061


**CODE** DE150\_27\_A



Kg/mt	5.27 Kg/mt
L	150 mm
H	27 mm
Rth,F	0.513 K/W
Rth,N	1.53 K/W
Alloy	6061




**CODE** DE150\_40



Kg/mt	7.42 Kg/mt
L	150 mm
H	40 mm
Rth,F	0.299 K/W
Rth,N	0.68 K/W
Alloy	6061

**CODE** DE150\_50




Kg/mt	9.58 Kg/mt
L	150 mm
H	50 mm
Rth,F	0.580 K/W
Rth,N	1.70 K/W
Alloy	6061

**CODE** DE150\_62




Kg/mt	12.33 Kg/mt
L	150 mm
H	62 mm
Rth,F	0.252 K/W
Rth,N	0.73 K/W
Alloy	6061

**CODE** DE150\_72




Kg/mt	8.934 Kg/mt
L	150 mm
H	72 mm
Rth,F	0.69 K/W
Rth,N	1.89 K/W
Alloy	6061

**CODE** DE150\_83



Kg/mt	12.33 Kg/mt
L	150 mm
H	83 mm
Rth,F	0.460 K/W
Rth,N	1.26 K/W
Alloy	6061


**CODE** DE115\_35



Kg/mt	2.15 Kg/mt
L	115 mm
H	35 mm
Rth,F	1.350 K/W
Rth,N	3.69 K/W
Alloy	6061




**CODE** DE160\_40




Kg/mt	8.64 Kg/mt
L	160 mm
H	40 mm
Rth,F	0.281 K/W
Rth,N	0.64 K/W
Alloy	6061

**CODE** DE160\_50




Kg/mt	8.86 Kg/mt
L	160 mm
H	50 mm
Rth,F	0.459 K/W
Rth,N	1.35 K/W
Alloy	6061

**CODE** DE162\_25



Kg/mt	5.23 Kg/mt
L	162 mm
H	25 mm
Rth,F	0.531 K/W
Rth,N	1.62 K/W
Alloy	6061

**CODE** DE164\_93.5




Kg/mt	19 Kg/mt
L	164 mm
H	93.5 mm
Rth,F	0.405 K/W
Rth,N	1.17 K/W
Alloy	6061

**CODE** DE173\_28




Kg/mt	4.22 Kg/mt
L	173 mm
H	28 mm
Rth,F	0.369 K/W
Rth,N	1.08 K/W
Alloy	6061

**CODE** DE178\_80




Kg/mt	12.782 Kg/mt
L	178 mm
H	80 mm
Rth,F	0.370 K/W
Rth,N	1.08 K/W
Alloy	6061

**CODE** DE180\_80




Kg/mt	12.78 Kg/mt
L	180 mm
H	80 mm
Rth,F	0.378 K/W
Rth,N	1.17 K/W
Alloy	6061

**CODE** DE188\_30




Kg/mt	7.36 Kg/mt
L	188 mm
H	30 mm
Rth,F	0.531 K/W
Rth,N	1.62 K/W
Alloy	6061

**CODE** DE190.5\_83




Kg/mt	14.83 Kg/mt
L	190.5 mm
H	83 mm
Rth,F	0.369 K/W
Rth,N	.08 K/W
Alloy	6061

**CODE** DE190.5\_83\_A




Kg/mt	14.75 Kg/mt
L	190.5 mm
H	83 mm
Rth,F	0.410 K/W
Rth,N	1.20 K/W
Alloy	6061

**CODE** DE190\_50.1




Kg/mt	6.799 Kg/mt
L	190 mm
H	50.1 mm
Rth,F	0.45 K/W
Rth,N	1.26 K/W
Alloy	6061

**CODE** DE197\_20




Kg/mt	5.64 Kg/mt
L	197 mm
H	20 mm
Rth,F	0.242 K/W
Rth,N	0.72 K/W
Alloy	6061

**CODE** DE200\_84




Kg/mt	17.74 Kg/mt
L	200 mm
H	84 mm
Rth,F	0.279 K/W
Rth,N	0.90 K/W
Alloy	6061

**CODE** DE200\_15




Kg/mt	3.90 Kg/mt
L	200 mm
H	15 mm
Rth,F	0.621 K/W
Rth,N	1.89 K/W
Alloy	6061

**CODE** DE200\_25




Kg/mt	5.38 Kg/mt
L	200 mm
H	25 mm
Rth,F	0.477 K/W
Rth,N	1.50 K/W
Alloy	6061

**CODE** DE200\_40




Kg/mt	9.72 Kg/mt
L	200 mm
H	40 mm
Rth,F	0.154 K/W
Rth,N	0.46 K/W
Alloy	6061

**CODE** DE200\_60




Kg/mt	15.16 Kg/mt
L	200 mm
H	60 mm
Rth,F	0.121 K/W
Rth,N	0.36 K/W
Alloy	6061

**CODE** DE200\_72




Kg/mt	14.53 Kg/mt
L	200 mm
H	72 mm
Rth,F	0.130 K/W
Rth,N	0.38 K/W
Alloy	6061

**CODE** DE200\_83




Kg/mt	19.9 Kg/mt
L	200 mm
H	83 mm
Rth,F	0.119 K/W
Rth,N	0.35 K/W
Alloy	6061

**CODE** DE200\_84



Kg/mt	17.74 Kg/mt
L	200 mm
H	84 mm
Rth,F	0.279 K/W
Rth,N	0.90 K/W
Alloy	6061

**CODE** DE200\_86




Kg/mt	19.17 Kg/mt
L	200 mm
H	86 mm
Rth,F	1.17 K/W
Rth,N	1.20 K/W
Alloy	6061

**CODE** DE210\_70




Kg/mt	19.99 Kg/mt
L	210 mm
H	68 mm
Rth,F	0.369 K/W
Rth,N	1.08 K/W
Alloy	6061

**CODE** DE215\_77




Kg/mt	22.15 Kg/mt
L	215 mm
H	77 mm
Rth,F	0.330 K/W
Rth,N	0.88 K/W
Alloy	6061

**CODE** DE215\_77




Kg/mt	19.80 Kg/mt
L	215 mm
H	77 mm
Rth,F	0.279 K/W
Rth,N	0.81 K/W
Alloy	6061

**CODE** DE216\_77




Kg/mt	24 Kg/mt
L	216 mm
H	77 mm
Rth,F	0.297 K/W
Rth,N	0.88 K/W
Alloy	6061

**CODE** DE216\_83




Kg/mt	18.06 Kg/mt
L	216 mm
H	83 mm
Rth,F	0.324 K/W
Rth,N	0.99 K/W
Alloy	6061

**CODE** DE220\_46.5




Kg/mt	11.27 Kg/mt
L	220 mm
H	46.5 mm
Rth,F	0.378 K/W
Rth,N	1.17 K/W
Alloy	6061

**CODE** DE220\_60




Kg/mt	16.719 Kg/mt
L	220 mm
H	60 mm
Rth,F	0.36 K/W
Rth,N	0.39 K/W
Alloy	6061

**CODE** DE220\_77



Kg/mt	17.54 Kg/mt
L	220 mm
H	77 mm
Rth,F	0.351 K/W
Rth,N	1.08 K/W
Alloy	6061


**CODE** DE226\_80



Kg/mt	23.74 Kg/mt
L	226 mm
H	80 mm
Rth,F	0.369 K/W
Rth,N	1.08 K/W
Alloy	6061




**CODE** DE228\_32.2



Kg/mt	8.132 Kg/mt
L	228 mm
H	32.2 mm
Rth,F	0.150 K/W
Rth,N	0.43 K/W
Alloy	6061

**CODE** DE235\_60




Kg/mt	14.893 Kg/mt
L	235 mm
H	60 mm
Rth,F	0.310 K/W
Rth,N	0.9 K/W
Alloy	6061

**CODE** DE240\_16




Kg/mt	5.57 Kg/mt
L	240 mm
H	16 mm
Rth,F	0.531 K/W
Rth,N	1.62 K/W
Alloy	6061

**CODE** DE240\_108\_A




Kg/mt	25.056 Kg/mt
L	240mm
H	108 mm
Rth,F	0.324 K/W
Rth,N	0.99 K/W
Alloy	6061

**CODE** DE240\_108\_B



Kg/mt	26.101 Kg/mt
L	240mm
H	108 mm
Rth,F	0.324 K/W
Rth,N	0.99 K/W
Alloy	6061

**CODE** DE240\_112



Kg/mt	29.824 Kg/mt
L	240mm
H	112 mm
Rth,F	0.345 K/W
Rth,N	1.05 K/W
Alloy	6061




**CODE DE245.6**



Kg/mt	6.39 Kg/mt
L	245.6 mm
H	0.423 K/W
Rth,F	1.26 K/W
Rth,N	25 mm
Alloy	6061

**CODE DE249\_75.6**




Kg/mt	15.841 Kg/mt
L	249 mm
H	75.6 mm
Rth,F	0.082 K/W
Rth,N	0.28 K/W
Alloy	6061

**CODE DE250\_40.5**




Kg/mt	10.97 Kg/mt
L	250 mm
H	40.50 mm
Rth,F	0.390 K/W
Rth,N	1.08 K/W
Alloy	6061

**CODE DE250\_40**




Kg/mt	11.94 Kg/mt
L	250 mm
H	40 mm
Rth,F	0.333 K/W
Rth,N	0.99 K/W
Alloy	6061

**CODE DE250\_40\_A**




Kg/mt	9.66 Kg/mt
L	250 mm
H	40 mm
Rth,F	0.390 K/W
Rth,N	1.08 K/W
Alloy	6061

**CODE DE250\_40\_D**




Kg/mt	13.22 Kg/mt
L	250 mm
H	40 mm
Rth,F	0.430 K/W
Rth,N	1.30 K/W
Alloy	6061

**CODE** DE250\_83



Kg/mt	24.68 Kg/mt
L	250 mm
H	83 mm
Rth,F	0.310 K/W
Rth,N	0.90 K/W
Alloy	6061

**CODE** DE260\_67.5




Kg/mt	20.68 Kg/mt
L	260 mm
H	67.50 mm
Rth,F	0.290 K/W
Rth,N	0.81 K/W
Alloy	6061

**CODE** DE260\_67.5\_A




Kg/mt	18.18 Kg/mt
L	260 mm
H	67.50 mm
Rth,F	0.279 K/W
Rth,N	0.90 K/W
Alloy	6061

**CODE** DE265\_74




Kg/mt	24.92 Kg/mt
L	265 mm
H	74 mm
Rth,F	0.297 K/W
Rth,N	0.88 K/W
Alloy	6061

**CODE** DE265\_74\_A




Kg/mt	24.13 Kg/mt
L	265 mm
H	74 mm
Rth,F	0.330 K/W
Rth,N	0.88 K/W
Alloy	6061

**CODE** DE270\_73




Kg/mt	18.74 Kg/mt
L	270 mm
H	73 mm
Rth,F	0.350 K/W
Rth,N	0.99 K/W
Alloy	6061

**CODE** DE290\_85




Kg/mt	25.40 Kg/mt
L	290 mm
H	0.279 K/W
Rth,F	0.81 K/W
Rth,N	85 mm
Alloy	6061

**CODE** DE300\_25\_A



Kg/mt	9.022 Kg/mt
L	300 mm
H	25 mm
Rth,F	0.398 K/W
Rth,N	1.28 K/W
Alloy	6061

**CODE** DE300\_25\_B




Kg/mt	9.01 Kg/mt
L	300 mm
H	25 mm
Rth,F	0.121 K/W
Rth,N	0.36 K/W
Alloy	6061

**CODE** DE300\_27




Kg/mt	11.90 Kg/mt
L	300 mm
H	27 mm
Rth,F	0.390 K/W
Rth,N	1.08 K/W
Alloy	6061

**CODE** DE300\_36



Kg/mt	11.285 Kg/mt
L	300 mm
H	36 mm
Rth,F	0.279 K/W
Rth,N	0.81 K/W
Alloy	6061

**CODE** DE300\_40




Kg/mt	13.02 Kg/mt
L	300 mm
H	40 mm
Rth,F	0.342 K/W
Rth,N	1.10 K/W
Alloy	6061

**CODE** DE300\_40\_A




Kg/mt	15.80 Kg/mt
L	300 mm
H	40 mm
Rth,F	0.351 K/W
Rth,N	1.08 K/W
Alloy	6061

**CODE** DE300\_40\_B




Kg/mt	14.35 Kg/mt
L	300 mm
H	40 mm
Rth,F	0.288 K/W
Rth,N	0.88 K/W
Alloy	6061

**CODE** DE300\_60




Kg/mt	20.53 Kg/mt
L	300 mm
H	60 mm
Rth,F	0.279 K/W
Rth,N	0.81 K/W
Alloy	6061

**CODE** DE300\_70.4




Kg/mt	18.77 Kg/mt
L	300 mm
H	70.4 mm
Rth,F	0.279 K/W
Rth,N	0.90 K/W
Alloy	6061

**CODE** DE300\_83\_A




Kg/mt	23.07 Kg/mt
L	300 mm
H	83 mm
Rth,F	0.261 K/W
Rth,N	0.81 K/W
Alloy	6061

**CODE** DE300\_84\_C




Kg/mt	24.99 Kg/mt
L	300 mm
H	84.50 mm
Rth,F	0.250 K/W
Rth,N	0.72 K/W
Alloy	6061

**CODE** DE300\_84




Kg/mt	28.44 Kg/mt
L	300 mm
H	84 mm
Rth,F	0.280 K/W
Rth,N	0.81 K/W
Alloy	6061

**CODE** DE300\_84\_A




Kg/mt	26.64 Kg/mt
L	300 mm
H	84 mm
Rth,F	0.230 K/W
Rth,N	0.63 K/W
Alloy	6061

**CODE** DE300\_84\_C




Kg/mt	24.99 Kg/mt
L	300 mm
H	84.50 mm
Rth,F	0.250 K/W
Rth,N	0.72 K/W
Alloy	6061

**CODE** DE315\_72.7\_A




Kg/mt	19.217 Kg/mt
L	315 mm
H	72.7 mm
Rth,F	0.23 K/W
Rth,N	0.63 K/W
Alloy	6061

**CODE** DE315\_72.7\_B



Kg/mt	15.466 Kg/mt
L	315 mm
H	72.7 mm
Rth,F	0.348 K/W
Rth,N	1.10 K/W
Alloy	6061


**CODE** DE345\_61.5



Kg/mt	20.07 Kg/mt
L	345 mm
H	61.5 mm
Rth,F	0.290 K/W
Rth,N	0.81 K/W
Alloy	6061




**CODE** DE362\_35




Kg/mt	11.13 Kg/mt
L	362 mm
H	35 mm
Rth,F	0.342 K/W
Rth,N	0.99 K/W
Alloy	6061

**CODE** DE380\_60\_E




Kg/mt	18.35 Kg/mt
L	380 mm
H	60 mm
Rth,F	0.243 K/W
Rth,N	0.72 K/W
Alloy	6061

**CODE** DE400\_40



Kg/mt	21.44 Kg/mt
L	400 mm
H	40 mm
Rth,F	0.279 K/W
Rth,N	0.81 K/W
Alloy	6061

**CODE** DE400\_61



Kg/mt	22.35 Kg/mt
L	400 mm
H	61 mm
Rth,F	0.290 K/W
Rth,N	0.81 K/W
Alloy	6061

**CODE** DE470\_83



Kg/mt	25.60 Kg/mt
L	470 mm
H	83 mm
Rth,F	0.087 K/W
Rth,N	0.23 K/W
Alloy	6061





# WELDED TECHNOLOGY


*To obtain profiles of large dimensions, which cannot be made directly with extrusion, two or more extruded profiles can be welded together.*

Welding is extremely flexible to the customer's dimensional needs and can be used for any modification to existing profiles. MG Italy makes its experience and availability available to its customers in order to create the required product.

---


We provide special extruded profiles already chamfered for a simpler and more efficient MIG and TIG welding operation. This technique allows us to create profiles with a maximum width of 900 mm.

**CODE DSAXX\_YY**




L	XX mm
H	YY mm
Alloy	6060

**CODE DSBXX\_YY**




L	XX mm
H	YY mm
Alloy	6060

**CODE DE207\_187.3**




Kg/mt	6 Kg/mt
L	207 mm
H	187.3 mm
Rth,F	0.127 K/W
Rth,N	0.39 K/W
Alloy	6061

**CODE DE320\_75.5**




Kg/mt	18.128 Kg/mt
L	320 mm
H	75.5 mm
Rth,F	0.27 K/W
Rth,N	0.80 K/W
Alloy	6061

**CODE DS340\_70.4**



Kg/mt	21.29 Kg/mt
L	340 mm
H	70.40 mm
Rth,F	0.261 K/W
Rth,N	0.81 K/W
Alloy	6061

**CODE DS360\_83.5**



Kg/mt	30.40 Kg/mt
L	360 mm
H	0.117 K/W
Rth,F	0.36 K/W
Rth,N	83.50 mm
Alloy	6061

**CODE DS398\_70.9**




Kg/mt	28.70 Kg/mt
L	398 mm
H	70.90 mm
Rth,F	0.63 K/W
Rth,N	0.60 K/W
Alloy	6061

**CODE DS400\_60**




Kg/mt	30.60 Kg/mt
L	400 mm
H	60 mm
Rth,F	0.117 K/W
Rth,N	0.36 K/W
Alloy	6061

**CODE DS400\_83**



Kg/mt	39.75 Kg/mt
L	400 mm
H	83 mm
Rth,F	0.63 K/W
Rth,N	0.60 K/W
Alloy	6061

**CODE DS400\_85**



Kg/mt	35.76 Kg/mt
L	400 mm
H	85 mm
Rth,F	0.190 K/W
Rth,N	0.54 K/W
Alloy	6061

**CODE DS430\_77\_A**



Kg/mt	39.60 Kg/mt
L	430 mm
H	77 mm
Rth,F	0.190 K/W
Rth,N	0.54 K/W
Alloy	6061

**CODE DS432\_77**



Kg/mt	48 Kg/mt
L	432 mm
H	77 mm
Rth,F	0.189 K/W
Rth,N	0.60 K/W
Alloy	6061

**CODE DS432\_83**




Kg/mt	36.13 Kg/mt
L	432 mm
H	83 mm
Rth,F	0.198 K/W
Rth,N	0.63 K/W
Alloy	6061

**CODE DS440\_60**



Kg/mt	34.54 Kg/mt
L	440 mm
H	60 mm
Rth,F	0.216 K/W
Rth,N	0.70 K/W
Alloy	6061

**CODE DS450\_85**



Kg/mt	40.13 Kg/mt
L	450 mm
H	85 mm
Rth,F	0.162 K/W
Rth,N	0.48 K/W
Alloy	6061

**CODE DS460\_80.5**



Kg/mt	34.95 Kg/mt
L	460 mm
H	80.50 mm
Rth,F	0.108 K/W
Rth,N	0.32 K/W
Alloy	6061

**CODE DS500\_40**




Kg/mt	23.87 Kg/mt
L	500 mm
H	40 mm
Rth,F	0.171 K/W
Rth,N	0.63 K/W
Alloy	6061

**CODE DS500\_83**



Kg/mt	49.36 Kg/mt
L	500 mm
H	83 mm
Rth,F	0.189 K/W
Rth,N	0.54 K/W
Alloy	6061

**CODE DS500\_85**



Kg/mt	44.51 Kg/mt
L	500 mm
H	85 mm
Rth,F	0.153 K/W
Rth,N	0.45 K/W
Alloy	6061

**CODE DS520\_67.5**



Kg/mt	41.36 Kg/mt
L	520 mm
H	67.50 mm
Rth,F	0.171 K/W
Rth,N	0.54 K/W
Alloy	6061

**CODE DS520\_67.5\_A**



Kg/mt	36.37 Kg/mt
L	520 mm
H	67.50 mm
Rth,F	0.190 K/W
Rth,N	0.54 K/W
Alloy	6061

**CODE DS550\_85**



Kg/mt	48.88 Kg/mt
L	550 mm
H	85 mm
Rth,F	0.150 K/W
Rth,N	0.45 K/W
Alloy	6061

**CODE DS600\_25**




Kg/mt	18.02 Kg/mt
L	600 mm
H	25 mm
Rth,F	0.252 K/W
Rth,N	0.80 K/W
Alloy	6061

**CODE DS600\_40\_A**



Kg/mt	31.60 Kg/mt
L	600 mm
H	40 mm
Rth,F	0.72 K/W
Rth,N	0.70 K/W
Alloy	6061

**CODE** DS600\_70.4



Kg/mt	37.53 Kg/mt
L	600 mm
H	70.40 mm
Rth,F	0.190 K/W
Rth,N	0.54 K/W
Alloy	6061

**CODE** DS600\_83\_A




Kg/mt	46.15 Kg/mt
L	600 mm
H	83 mm
Rth,F	0.162 K/W
Rth,N	0.48 K/W
Alloy	6061

**CODE** DS600\_85



Kg/mt	53.25 Kg/mt
L	600 mm
H	85 mm
Rth,F	0.135 K/W
Rth,N	0.40 K/W
Alloy	6061

**CODE** DS690\_61.5



Kg/mt	40.15 Kg/mt
L	690 mm
H	61.50 mm
Rth,F	0.171 K/W
Rth,N	0.54 K/W
Alloy	6061

**CODE** DS700\_85



Kg/mt	62 Kg/mt
L	700 mm
H	85 mm
Rth,F	0.13 K/W
Rth,N	0.36 K/W
Alloy	6061

**CODE** DS750\_85



Kg/mt	66.37 Kg/mt
L	750 mm
H	85 mm
Rth,F	0.117 K/W
Rth,N	0.36 K/W
Alloy	6061




**CODE DS800\_40**



Kg/mt	42.87 Kg/mt
L	800 mm
H	40 mm
Rth,F	0.171 K/W
Rth,N	0.54 K/W
Alloy	6061

**CODE DS800\_85**



Kg/mt	70.75 Kg/mt
L	800 mm
H	85 mm
Rth,F	0.108 K/W
Rth,N	0.32 K/W
Alloy	6061

**CODE DS850\_85**





Kg/mt	75.12 Kg/mt
L	850 mm
H	85 mm
Rth,F	0.108 K/W
Rth,N	0.32 K/W
Alloy	6061

**CODE DS900\_85**



Kg/mt	79.49 Kg/mt
L	900 mm
H	85 mm
Rth,F	0.099 K/W
Rth,N	0.32 K/W
Alloy	6061



# ASSEMBLED TECHNOLOGY

*This line of products was born from the continuous and growing need to supply heat sinks with ever greater thermal performance.*


We worked on the section of the single fin, on the number of fins and on their arrangement. Obtained by mechanically assembling the single fins, the high efficiency heat sinks also offer high dimensional flexibility and the same mechanical characteristics as the extruded heat sinks, making them particularly

---

suitable for use in high power systems in forced convection.


Defined Assembled Profiles (PA) are divided by width and height of the single fin profile or module and organized in increasing order of size.

**CODE** **DAAXX\_YY**




<b>L</b>	XX mm
<b>H</b>	YY mm
<b>Alloy</b>	1050

**CODE** **DABXX\_YY**




<b>L</b>	XX mm
<b>H</b>	YY mm
<b>Alloy</b>	1050

**CODE** **DACXX\_YY**




<b>L</b>	XX mm
<b>H</b>	YY mm
<b>Alloy</b>	1050

**CODE** **DADXX\_YY**




<b>L</b>	XX mm
<b>H</b>	YY mm
<b>Alloy</b>	1050

**CODE** **DAEXX\_YY**




<b>L</b>	XX mm
<b>H</b>	YY mm
<b>Alloy</b>	1050

**CODE** **DAFXX\_YY**



<b>L</b>	XX mm
<b>H</b>	YY mm
<b>Alloy</b>	1050

**CODE** **AE3.5\_41.5**



<b>Kg/mt</b>	0.28 Kg/mt
<b>L</b>	3.50 mm
<b>H</b>	41.50 mm
<b>Alloy</b>	6061

**CODE** **AE4.5\_65**



<b>Kg/mt</b>	0.77 Kg/mt
<b>L</b>	4.50 mm
<b>H</b>	65 mm
<b>Alloy</b>	6061

**CODE** **AE4.5\_70**




<b>Kg/mt</b>	0.39 Kg/mt
<b>L</b>	4.50 mm
<b>H</b>	70 mm
<b>Alloy</b>	6061

**CODE** **AE4.5\_76**




<b>Kg/mt</b>	0.47 Kg/mt
<b>L</b>	4.50 mm
<b>H</b>	76 mm
<b>Alloy</b>	6061

**CODE** **AE5.5\_90**




<b>Kg/mt</b>	0.81 Kg/mt
<b>L</b>	5.50 mm
<b>H</b>	90 mm
<b>Alloy</b>	6061

**CODE** **AE5.5\_125**




<b>Kg/mt</b>	1.06 Kg/mt
<b>L</b>	5.50 mm
<b>H</b>	125 mm
<b>Alloy</b>	6061

**CODE AE5.5\_54**




<b>Kg/mt</b>	0.61 Kg/mt
<b>L</b>	5.50 mm
<b>H</b>	54 mm
<b>Alloy</b>	6061

**CODE AE5.5\_61.2**




<b>Kg/mt</b>	0.44 Kg/mt
<b>L</b>	5.50 mm
<b>H</b>	61.20 mm
<b>Alloy</b>	6061

**CODE AE5.5\_75**




<b>Kg/mt</b>	0.45 Kg/mt
<b>L</b>	5.50 mm
<b>H</b>	75 mm
<b>Alloy</b>	6061

**CODE AE5.5\_105**




<b>Kg/mt</b>	0.83 Kg/mt
<b>L</b>	5.50 mm
<b>H</b>	105 mm
<b>Alloy</b>	6061

**CODE AE5.5\_90**




<b>Kg/mt</b>	0.87 Kg/mt
<b>L</b>	5.50 mm
<b>H</b>	90 mm
<b>Alloy</b>	6061

**CODE AE5.5\_125**



<b>Kg/mt</b>	1.37 Kg/mt
<b>L</b>	5.50 mm
<b>H</b>	125 mm
<b>Alloy</b>	6061

**CODE AE5.8\_77**



<b>Kg/mt</b>	0.75 Kg/mt
<b>L</b>	5.80 mm
<b>H</b>	77 mm
<b>Alloy</b>	6061

**CODE AE5.9\_100**




<b>Kg/mt</b>	0.69 Kg/mt
<b>L</b>	5.90 mm
<b>H</b>	100 mm
<b>Alloy</b>	6061

**CODE AE5\_41.50**




<b>Kg/mt</b>	0.29 Kg/mt
<b>L</b>	5 mm
<b>H</b>	41.5 mm
<b>Alloy</b>	6061

**CODE AE6.3\_77**




<b>Kg/mt</b>	0.50 Kg/mt
<b>L</b>	6.30 mm
<b>H</b>	77 mm
<b>Alloy</b>	6061

**CODE AE6\_90**



<b>Kg/mt</b>	0.68 Kg/mt
<b>L</b>	6 mm
<b>H</b>	90 mm
<b>Alloy</b>	6061

**CODE AE6\_125**



<b>Kg/mt</b>	0.86 Kg/mt
<b>L</b>	6 mm
<b>H</b>	125 mm
<b>Alloy</b>	6061




**CODE AE6\_57**



<b>Kg/mt</b>	0.51 Kg/mt
<b>L</b>	6 mm
<b>H</b>	57 mm
<b>Alloy</b>	6061

**CODE AE6\_62**



<b>Kg/mt</b>	0.44 Kg/mt
<b>L</b>	6 mm
<b>H</b>	62 mm
<b>Alloy</b>	6061

**CODE AE6\_75**



<b>Kg/mt</b>	0.51 Kg/mt
<b>L</b>	6 mm
<b>H</b>	75 mm
<b>Alloy</b>	6061

**CODE AE6\_117**



<b>Kg/mt</b>	0.81 Kg/mt
<b>L</b>	6 mm
<b>H</b>	117 mm
<b>Alloy</b>	6061

**CODE AE6\_127**



<b>Kg/mt</b>	0.96 Kg/mt
<b>L</b>	6 mm
<b>H</b>	127 mm
<b>Alloy</b>	6061

**CODE AE6\_90**




<b>Kg/mt</b>	0.77 Kg/mt
<b>L</b>	6 mm
<b>H</b>	90 mm
<b>Alloy</b>	6061

**CODE** AE6\_125




<b>Kg/mt</b>	0.98 Kg/mt
<b>L</b>	6 mm
<b>H</b>	125 mm
<b>Alloy</b>	6061

**CODE** DA7.6\_77.5




<b>L</b>	7.60 mm
<b>H</b>	77.50 mm
<b>Rth,F</b>	0.270 K/W
<b>Rth,N</b>	0.80 K/W
<b>Alloy</b>	1050

**CODE** DA7.6\_100




<b>L</b>	7.60 mm
<b>H</b>	100 mm
<b>Rth,F</b>	0.216 K/W
<b>Rth,N</b>	0.63 K/W
<b>Alloy</b>	6061

**CODE** DA8\_55



<b>L</b>	8 mm
<b>H</b>	55 mm
<b>Rth,F</b>	0.360 K/W
<b>Rth,N</b>	0.99 K/W
<b>Alloy</b>	1050

**CODE** DA8\_62



<b>L</b>	8 mm
<b>H</b>	62 mm
<b>Rth,F</b>	0.297 K/W
<b>Rth,N</b>	0.88 K/W
<b>Alloy</b>	1050

**CODE** AE9\_54




<b>Kg/mt</b>	0.63 Kg/mt
<b>L</b>	9 mm
<b>H</b>	54 mm
<b>Alloy</b>	6061

**CODE** AE9\_61.2




<b>Kg/mt</b>	0.67 Kg/mt
<b>L</b>	9 mm
<b>H</b>	61.2 mm
<b>Alloy</b>	6061

**CODE** DA9\_83.5



<b>L</b>	9 mm
<b>H</b>	83.50 mm
<b>Rth,F</b>	0.320 K/W
<b>Rth,N</b>	0.88 K/W
<b>Alloy</b>	1050

**CODE** DA10\_117




<b>L</b>	10 mm
<b>H</b>	0.70 K/W
<b>Rth,F</b>	0.240 K/W
<b>Rth,N</b>	117 mm
<b>Alloy</b>	1050

**CODE** DA10\_122




<b>L</b>	10 mm
<b>H</b>	122 mm
<b>Rth,F</b>	0.230 K/W
<b>Rth,N</b>	0.63 K/W
<b>Alloy</b>	1050

**CODE** AE10\_127




<b>Kg/mt</b>	2.52 Kg/mt
<b>L</b>	10 mm
<b>H</b>	127 mm
<b>Alloy</b>	6061

**CODE** DA10\_65




<b>L</b>	10 mm
<b>H</b>	65 mm
<b>Rth,F</b>	0.99 K/W
<b>Rth,N</b>	0.360 K/W
<b>Alloy</b>	1050

**CODE DA10\_71**




L	10 mm
H	71 mm
Rth,F	1.08 K/W
Rth,N	0.369 K/W
Alloy	1050

**CODE DA10\_75**



L	10 mm
H	75 mm
Rth,F	0.90 K/W
Rth,N	0.279 K/W
Alloy	1050

**CODE DA10\_78**




L	10 mm
H	78 mm
Rth,F	0.320 K/W
Rth,N	0.88 K/W
Alloy	1050

**CODE DA10\_81**



L	10 mm
H	81 mm
Rth,F	0.279 K/W
Rth,N	0.81 K/W
Alloy	1050

**CODE DA10\_85**




L	10 mm
H	85 mm
Rth,F	0.81 K/W
Rth,N	0.252 K/W
Alloy	1050

**CODE DA10\_90**



L	10 mm
H	90 mm
Rth,F	0.90 K/W
Rth,N	0.279 K/W
Alloy	1050

**CODE DA10\_101**



<b>L</b>	10 mm
<b>H</b>	101 mm
<b>Rth,F</b>	0.279 K/W
<b>Rth,N</b>	0.81 K/W
<b>Alloy</b>	1050


**CODE DA10\_132.5**

Kg/mt 1.434



<b>L</b>	10 mm
<b>H</b>	132.50 mm
<b>Rth,F</b>	0.210 K/W
<b>Rth,N</b>	0.56 K/W
<b>Alloy</b>	1050

**CODE AE12.5\_125**



<b>Kg/mt</b>	1.38 Kg/mt
<b>L</b>	12.50 mm
<b>H</b>	125 mm
<b>Alloy</b>	6061

**CODE AC12\_90**



<b>Kg/mt</b>	1.40 Kg/mt
<b>L</b>	12 mm
<b>H</b>	90 mm
<b>Rth,F</b>	100 K/W

**CODE AE12\_90**



<b>Kg/mt</b>	1.40 Kg/mt
<b>L</b>	12 mm
<b>H</b>	90 mm
<b>Alloy</b>	6061

**CODE AE12\_105**



<b>Kg/mt</b>	1.53 Kg/mt
<b>L</b>	12 mm
<b>H</b>	105 mm
<b>Alloy</b>	6061



**CODE** AE12\_117




<b>Kg/mt</b>	1.64 Kg/mt
<b>L</b>	12 mm
<b>H</b>	117 mm
<b>Alloy</b>	6061

**CODE** AE12\_125



<b>Kg/mt</b>	1.76 Kg/mt
<b>L</b>	12 mm
<b>H</b>	125 mm
<b>Alloy</b>	6061

**CODE** DA12\_125




<b>L</b>	12 mm
<b>H</b>	125 mm
<b>Rth,F</b>	0.220 K/W
<b>Rth,N</b>	0.63 K/W
<b>Alloy</b>	1050

**CODE** DA12\_127



<b>L</b>	12 mm
<b>H</b>	127 mm
<b>Rth,F</b>	0.250 K/W
<b>Rth,N</b>	0.72 K/W
<b>Alloy</b>	1050

**CODE** AE13.79\_84




<b>Kg/mt</b>	1.52 Kg/mt
<b>L</b>	13.79 mm
<b>H</b>	84 mm
<b>Alloy</b>	6061

**CODE** DA15\_118




<b>L</b>	15 mm
<b>H</b>	118 mm
<b>Rth,F</b>	0.81 K/W
<b>Rth,N</b>	0.290 K/W
<b>Alloy</b>	1050

**CODE** A20\_41




<b>Kg/mt</b>	1.08 Kg/mt
<b>L</b>	20 mm
<b>H</b>	41 mm
<b>Alloy</b>	6061

**CODE** AE25\_41



<b>Kg/mt</b>	1.52 Kg/mt
<b>L</b>	25 mm
<b>H</b>	41 mm
<b>Alloy</b>	6061

**CODE** AE37.24\_84



<b>Kg/mt</b>	3.16 Kg/mt
<b>L</b>	37.24 mm
<b>H</b>	84 mm
<b>Alloy</b>	6061

**CODE** DA50\_62




<b>L</b>	50 mm
<b>H</b>	62 mm
<b>Rth,F</b>	0.220 K/W
<b>Rth,N</b>	0.63 K/W
<b>Alloy</b>	1050

**CODE** DE84\_6.6




<b>Kg/mt</b>	0.54
<b>L</b>	84 mm
<b>H</b>	6.6 mm
<b>Alloy</b>	6061

**CODE** DE84\_7.1



<b>Kg/mt</b>	0.97 Kg/mt
<b>L</b>	84 mm
<b>H</b>	7.1 mm
<b>Alloy</b>	6061

**CODE** DA95\_70.5




L	95 mm
H	70.50 mm
Rth,F	0.480 K/W
Rth,N	1.40 K/W
Alloy	1050

**CODE** AC100,5-12,5




Kg/mt	1.3 Kg/mt
L	100,5 mm
H	12.5 mm
Alloy	6060

**CODE** DE125\_10.1




Kg/mt	1.35 Kg/mt
L	125 mm
H	10.1 mm
Alloy	6061

**CODE** DE140\_125




Kg/mt	22.9 Kg/mt
L	140 mm
H	125 mm
Rth,F	0.18 K/W
Rth,N	0.81 K/W
Alloy	6061

**CODE** DE150\_125




Kg/mt	23.77 Kg/mt
L	150 mm
H	125 mm
Rth,F	0.128 K/W
Rth,N	0.38 K/W
Alloy	6061

**CODE** AE190.5\_83




Kg/mt	18.87 Kg/mt
L	190.50 mm
H	83 mm
Rth,F	0.260 K/W
Rth,N	0.72 K/W
Alloy	6061

**CODE** DE200\_125\_B





Kg/mt	30.8 Kg/mt
L	200 mm
H	125 mm
Rth,F	0.088 K/W
Rth,N	0.26 K/W
Alloy	6061

**CODE** DE200\_125\_A



Kg/mt	24.440 Kg/mt
L	200 mm
H	125 mm
Rth,F	0.088 K/W
Rth,N	0.26 K/W
Alloy	6061




# HEATSINK - PLUS

## TECHNOLOGY


---

**CODE** **HA100\_40**




<b>Kg/mt</b>	5.21 Kg/mt
<b>L</b>	100 mm
<b>H</b>	40 mm
<b>Alloy</b>	6061

**CODE** **HA150\_60**




<b>Kg/mt</b>	11.18 Kg/mt
<b>L</b>	150 mm
<b>H</b>	60 mm
<b>Alloy</b>	6061

**CODE** **HA200\_70**



<b>Kg/mt</b>	17.60 Kg/mt
<b>L</b>	200 mm
<b>H</b>	70 mm
<b>Alloy</b>	6061


**CODE** **HA250\_85**



<b>L</b>	250 mm
<b>H</b>	85 mm
<b>Alloy</b>	6061




**CODE** HA300\_85




<b>Kg/mt</b>	32.85 Kg/mt
<b>L</b>	300 mm
<b>H</b>	85 mm
<b>Alloy</b>	6061

**CODE** HA300\_135




<b>Kg/mt</b>	46.47 Kg/mt
<b>L</b>	300 mm
<b>H</b>	135 mm
<b>Alloy</b>	6061

**CODE** HA350\_75




<b>L</b>	350 mm
<b>H</b>	75 mm
<b>Alloy</b>	6061

**CODE** HA400\_85




<b>L</b>	400 mm
<b>H</b>	85 mm
<b>Alloy</b>	6061

**CODE HA500\_100**




<b>L</b>	500 mm
<b>H</b>	100 mm
<b>Alloy</b>	6061

**CODE HA600\_85**




<b>Kg/mt</b>	62.02 Kg/mt
<b>L</b>	600 mm
<b>H</b>	85 mm
<b>Alloy</b>	6061

**CODE HA700\_100**




<b>Kg/mt</b>	87.37 Kg/mt
<b>L</b>	700 mm
<b>H</b>	100 mm
<b>Alloy</b>	6061

**CODE HA800\_135**




<b>Kg/mt</b>	140.70 Kg/mt
<b>L</b>	800 mm
<b>H</b>	135 mm
<b>Alloy</b>	6061



# **WATER** **TECHNOLOGY**


---

**CODE** DA90\_20




<b>L</b>	90 mm
<b>H</b>	20 mm
<b>Alloy</b>	6060

**CODE** DA180\_20




<b>L</b>	180 mm
<b>H</b>	20 mm
<b>Alloy</b>	6060

**CODE** DA360\_20



<b>L</b>	360 mm
<b>H</b>	20 mm
<b>Alloy</b>	6060

**CODE** DA360\_20



<b>L</b>	360 mm
<b>H</b>	20 mm
<b>Alloy</b>	6060



# **MGSKIVED** **TECHNOLOGY**

---



## NEW DISSIPATION TECHNOLOGY

# MGSKIVED HEATSINKS

MGSKIVED technology is used when fins intensity cannot be achieved through extrusion technology. We can use both copper and aluminum.

Today, this technology allows us to overcome the limitations of the thickness and length ratio of conventional heat sinks, and our machines can produce high-density, very high-efficiency heat sinks. We can create tall and extremely thin fin-heat sinks with a long structure thanks to our dedicated beveling machines, using high-precision beveling cutting technology.

Our machines use a single block of material such as copper or aluminum. The fins and base become a “whole”.

Therefore the efficiency of the heat sink with extended fins is up to two times higher than the traditional heat sink.

Thermal conductivity efficiency can reach 100% of the profile material. This technology can be applied in the photovoltaic industry, electric vehicles, inverters, communication products, LED lights.

### General Specifications

Heat Sink Width (W)	max 3000 mm
Heat Sink Length (L)	max 580 mm
Heat Sink Height (H)	max 120 mm
Fin Thickness (FT)	0,3+1 mm
Fin Pitch (FD)	min 1,5 mm
Material	Aluminum, Copper





# **PV** **PROFILES**

---



**CODE SC-467-90**

Central support kit




**CODE PF-REGO-50**


Universal standard end clamp H 29 mm to 50 mm




**CODE TB 05608**




**CODE TB 09870**




**CODE TB 39061**




**CODE TB 39062**



**CODE TB 40381**





**CODE TB 40669**





CODE **TB 40692**

CODE **TB 40838**



CODE **TB 40905**

CODE **TB 40922**



EXTRUDED  
HEATSINKS

WELDING  
HEATSINKS

ASSEMBLED  
HEATSINKS

HEAT SINK PLUS  
HEATSINKS

WATER  
HEATSINKS

PV  
PROFILES


The technical drawing shows two views of a mechanical component. The top view (front view) has overall dimensions of 47 mm by 28 mm. It features a central horizontal slot with a width of 9.75 mm and a depth of 4.5 mm. There are four rounded corners with radii R0.8. The bottom view (side view) shows the profile of the part with a total height of 25.5 mm. It includes a central vertical feature with a width of 12.3 mm and a height of 8 mm. Various other dimensions specify the positions and sizes of different sections and fillets throughout the part.

Technical drawing of a mechanical part with dimensions in mm. The drawing shows a cross-section of a component with a central vertical slot and a horizontal base. Key dimensions include: overall width 56 mm, overall height 12.8 mm, central slot width 20.4 mm, and various radii (R10, R1, R0.75).


Technical drawing of a mechanical part, showing dimensions and tolerances. The drawing includes the following dimensions and features:

- Overall width: 55,98
- Overall height: 19,2
- Top width segments: 25,34, 19,8, 2,4, 0,5, 2,4
- Left side segments: 8, 5,3, 5,9, 2,7, 2
- Internal width segments: 8,45, 1,72, 6,04, 0,83
- Internal height segments: 16,2, 6,37, 7,55, 1,25
- Bottom width segments: 9,48, 2,76, 15, 17,44, 18,04
- Radiuses: R0,5, R0,74, R10, R1
- Angles: 30°, 3°
- Dimension lines and arrows indicating measurements.


**CODE TB 40985**




**CODE TB 41025**



**CODE TB 41026**



**CODE TB 41092**



EXTRUDED  
HEATSINKS

WELDING  
HEATSINKS

ASSEMBLED  
HEATSINKS


HEAT SINK PLUS  
HEATSINKS

WATER  
HEATSINKS


PV  
PROFILES




**CODE** **TB 41176**




**CODE** **TB 41367**




**CODE** **TB 41187**



CODE **TB 41539**



CODE **TB 41590**



EXTRUDED  
HEATSINKS

WELDING  
HEATSINKS

ASSEMBLED  
HEATSINKS


HEAT SINK PLUS  
HEATSINKS

WATER  
HEATSINKS


PV  
PROFILES

[illegible][illegible]


**CODE TB 41970**






**CODE TB 41971**





**CODE TB 41972**




**CODE** **TB 41174**



CODE **TB 41977**



CODE **TB 41978**



EXTRUDED  
HEATSINKS

WELDING  
HEATSINKS

ASSEMBLED  
HEATSINKS



HEAT SINK PLUS  
HEATSINKS

WATER  
HEATSINKS

PV  
PROFILES



**CODE** **TB 41980**

**CODE** **TB 41994**



# Processes & MACHINING

*MG ITALY carries out countless processes in order to obtain finished products of the highest quality*

---

- ◆ Cut
- ◆ CNC Technology
- ◆ Die Casting
- ◆ Surface treatments
- ◆ Assemblies



# Processes



## CUT

MG has a constantly updated fleet of machines and has over 7 systems dedicated solely to cutting operations. Covering a processing range from diameter 6mm to 200mm with a thickness of a few tenths up to the solid. In addition to round bars, we cut all types of shapes.

Several plants perform operations such as wire brush deburring (brushing), tap/die chamfering and rolling, threading, boring, turning, tapering and washing in line.

The materials we commonly work are carbon steel (iron), aluminum and its alloys (6060, ergal, etc.), copper, brass and stainless steel in various alloys (AISI 304 – AISI 316 – INCONEL – DUPLEX – SUPER DUPLEX etc.).

Thanks to the very modern machinery we are able to make cuts of various degrees, according to the customer's needs.



Wheel Cut



Band cut



## SURFACE TREATMENTS

Within its headquarters, the company has machinery for: metal burnishing, surface sandblasting, metal chrome plating, metal galvanizing, detail polishing.



Painting



Silk printing



## DIE-CASTING



Die casting



Sand casting



## CNC TECHNOLOGY

With a fleet of over 15 high-level machining centers, MG proposes itself as prime contractor for carrying out mechanical machining to customer drawings, guaranteeing the production of high precision parts with limited times and costs.

All the CNC machines always work manned by assigned personnel who are exclusively responsible for the good execution and dimensional control of the product they are making.


To make this way of working possible, the department heads supervise the production cycle, while other qualified personnel carry out some necessary and fundamental operations.



Milling



Turning



Laser cutting



Punching



Bending



## ASSEMBLY

To complete our mechanical processes, thanks to the know-how and experience acquired, our company is now specialized in the construction, assembly and assembly of groups for industrial plants and machinery.

We also carry out assembly of groups of equipment, carried out internally following the specific requests, guaranteeing care, attention and quality that our major customers recognize us after years of collaboration.




Mechanical assembly




Welding

# Notes







YOUR PARTNER IN METALWORKING


MG philosophy:

***“Competition is not about what  
companies produce, but about what  
they are able to add to the product”***



YOUR PARTNER IN METALWORKING





**MG ITALY**  
YOUR PARTNER IN METALWORKING

Barcelona  
Spain  
Calle Perú,  
186 bis 08020

**MG ITALY**  
YOUR PARTNER IN METALWORKING

Arezzo  
Italy  
Via La Minierina, 10  
Loc. Meleto 52022  
Cavriglia

**MG ITALY**  
YOUR PARTNER IN METALWORKING

DACH-Region  
Germany  
Riedelsbach 61, 94089  
Neureichenau

#### GERMANIA & AUSTRIA & SVIZZERA:

Sales Representative DACH Region  
Mr. Uwe Rüttgers

✉ uwe.ruettgers@mgitaly.it

☎ +49 160 90 667 850

#### SPAGNA & PORTOGALLO

Sales Representative Region  
Mr. Carlos Bausà

✉ carlos.bausa@mgitaly.it

☎ +34 611 706 967

#### ITALIA & FRANCIA

Sales Representative Region  
Mr. Giovanni Arcidiacono

✉ Giovanni.arcidiacono@mgitaly.it

☎ +39 055 91 23 830

**MG ITALY**  
YOUR PARTNER IN METALWORKING

**www.mgitaly.it**

### Servizio clienti:



Phone: +39 055 91 23 830  
Fax: 055 91 24 139



Service-eu@mgitaly.it



Via La Minierina n° 10  
52022 Cavriglia  
ITALIA (AR)



MGItaly ti invita a unirti alla sua visione eco-friendly: fruisce del nostro catalogo in formato digitale e riduci l'impatto ambientale.